



ENERG



енергия · ενεργεια



100778HSV941

alpha innotec

LWAV+ 82R1/3-HSV 9M1/3



Two icons showing sound power levels. The top icon shows a speaker inside a house with the text "44 dB". The bottom icon shows a speaker outside a house with the text "50 dB".



Legend for power consumption: a dark blue square for 5 kW, a medium blue square for 6 kW, and a light blue square for 6 kW.

Icon showing a clock and a coin with an arrow pointing to it, representing energy saving or cost reduction.





ENERGY

100778HSV941

alpha innotec

LWAV+ 82R1/3-HSV 9M1/3



Two icons showing sound power levels. The top icon shows a speaker inside a house with the value **44 dB**. The bottom icon shows a speaker outside a house with the value **50 dB**.




- 5 kW
- 6 kW
- 6 kW

An icon showing a clock face with a dashed line indicating a cycle, and a stack of coins with an arrow pointing down, representing energy consumption and cost.



ENERG

енергия · ενεργεια



100778HSV941

alpha innotec

LWAV+ 82R1/3-HSV 9M1/3 + Luxtronik 2.1

A+++
A++
A+
A
B
C
D
E
F
G

A+++
A++
A+
A
B
C
D
E
F
G

package (heat pumps and combination heater with heat pump) LWAV+ 82R1/3-HSV 9M1/3 + Luxtronik 2.1

Seasonal space heating energy efficiency of heat pump (η_s)

① 135 %

Rated heat output of the heat pump (P_{rated} kW)

6

Temperature control

Class

VII (Table 1)

+

② 3,5 %

Supplementary boiler

package with hot water storage tank

no

P_{sup} kW (rated heat output of supplementary heater)

η_s % (σ_{π})

$(\eta_s \% (sup) - ①) \times (\alpha_{WP}) = -$ ③ %

(α_{WE} : see Table 3)

(α_{WE})

solar contribution

(A_{Koll} m²)

(η_{Koll} %)

(V_{Sp} m³)

(standstill heat loss of the hot water storage tank in W)

(η_{Sp} : Table 2)


$((294/P_{rated} \times 11) \times (A_{Koll} \text{ m}^2) + (115/P_{rated} \times 11) \times (V_{Sp} \text{ m}^3)) \times 0,45 \times ((\eta_{Koll} \%)/100) \times (\eta_{Sp}) = +$ ④ %

Seasonal space heating energy efficiency of package

⑤ 138 %

rounded to the nearest integer

Seasonal space heating energy efficiency class of package



Seasonal space heating energy efficiency under colder or warmer climate conditions

Seasonal space heating energy efficiency of the heat pump (η_s) under colder climate conditions

127 %

Seasonal space heating energy efficiency of the heat pump (η_s) under warmer climate conditions

156 %

colder ⑤ 138 -V 7 = 131 warmer ⑤ 138 +VI 22 = 160

heatpump datasheet:			
manufacturer:	alpha innotec		
model:	LWAV+ 82R1/3-HSV 9M1/3		
Information concerning energy efficiency class and rated heat output:			
load profile water heating	XL		-
	average / low	average / medium	
energy efficiency class space heater:	A+++	A++	-
energy efficiency class waterheating	A		-
rated heat output:	7	6	kW
annual final energy consumption space heater	3029	3390	kWh
annual electricity consumption waterheating	1948		kWh
energy efficiency space heater:	180	135	%
energy efficiency waterheating	86		%
sound power level indoors	44		dB
special precautions concerning assembly, installation or maintenance			
All instructional work in this manual may only be carried out by qualified specialist personnel in compliance with local regulations.			
additional information	low	medium	
rated heat output colder climate	7	5	kW
rated heat output warmer climate	4	6	kW
annual energy consumption space heater colder climate	4339	3781	kWh
annual energy consumption space heater warmer climate	1009	1844	kWh
ann. Electricity consumption waterheating colder climate	2148		kWh
ann. Electricity consumption waterheating warmer climate	1692		kWh
energy efficiency space heater colder climate	145	127	%
energy efficiency space heater warmer climate	214	156	%
energy efficiency waterheating colder climate	78		%
energy efficiency DHWwarmer climate	99		%
sound power level outdoors	50		dB

technical data of the temperature controller		
manufacturer:	alpha innotec	
model:	Luxtronik 2.1	
controller class	VII	-
contribution of the controller to the energy efficiency space heater	3,5	%

Model				LWAV+ 82R1/3-HSV 9M1/3			
Air-to-water heat pump: (yes/no)				yes			
Brine-to-water heat pump: (yes/no)				no			
Water-to-water heat pump: (yes/no)				no			
Low-temperature heat pump: (yes/no)				no			
Equipped with supplementary heater: (yes/no)				yes			
combination heater with: (yes/no)				yes			
application: (low/medium)				medium			
climate: (colder/average/warmer)				average			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output	Prated	6	kW	Seasonal space heating energy efficiency	η_S	134,7	%
Declared coefficient of performance for part load at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	5,0	kW	Tj = -7°C	COPd	2,31	-
Tj = +2°C	Pdh	3,5	kW	Tj = +2°C	COPd	3,43	-
Tj = +7°C	Pdh	3,0	kW	Tj = +7°C	COPd	4,86	-
Tj = +12°C	Pdh	3,4	kW	Tj = +12°C	COPd	6,56	-
Tj = bivalent temperature	Pdh	5,0	kW	Tj = bivalent temperature	COPd	2,31	-
Tj = operation limit temperature	Pdh	4,2	kW	Tj = operation limit temperature	COPd	2,12	-
For air-to-water heat pumps: Tj = -15°C (if TOL < -20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C (if TOL < -20°C)	COPd	-	-
Bivalent temperature	T _{biv}	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Pcyc	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient (**)	Cdh	1,0	-	Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0,031	kW	Rated heat output	P _{sup}	1,4	kW
Thermostat-off mode	P _{TO}	-	kW	Type of energy input	electrical		
Standby mode	P _{SB}	0,031	kW				
Crankcase heater mode	P _{CK}	-	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	2.500	m ³ /h
sound power level, indoors/outdoors	L _{WA}	44 / 50	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h
Emissions of nitrogen oxides	NO _x	-	mg/kWh				
For heat pump combination heater:							
Declared load profile	XL			Water heating energy efficiency	η_{wh}	86	%
Daily electricity consumption	Q _{elec}	8,870	kWh	Daily fuel consumption	Q _{fuel}	-	kWh
Contact details	ait deutschland GmbH Industriestr. 3 95359 Kasendorf Germany						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).							
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							

Model				LWAV+ 82R1/3-HSV 9M1/3			
Air-to-water heat pump: (yes/no)				yes			
Brine-to-water heat pump: (yes/no)				no			
Water-to-water heat pump: (yes/no)				no			
Low-temperature heat pump: (yes/no)				no			
Equipped with supplementary heater: (yes/no)				yes			
combination heater with: (yes/no)				yes			
application: (low/medium)				low			
climate: (colder/average/warmer)				average			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output	Prated	7	kW	Seasonal space heating energy efficiency	η_S	179,8	%
Declared coefficient of performance for part load at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	5,9	kW	Tj = -7°C	COPd	3,26	-
Tj = +2°C	Pdh	3,8	kW	Tj = +2°C	COPd	4,70	-
Tj = +7°C	Pdh	3,3	kW	Tj = +7°C	COPd	5,97	-
Tj = +12°C	Pdh	3,4	kW	Tj = +12°C	COPd	7,92	-
Tj = bivalent temperature	Pdh	5,9	kW	Tj = bivalent temperature	COPd	3,26	-
Tj = operation limit temperature	Pdh	5,1	kW	Tj = operation limit temperature	COPd	3,18	-
For air-to-water heat pumps: Tj = -15°C (if TOL < -20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C (if TOL < -20°C)	COPd	-	-
Bivalent temperature	T _{biv}	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Pcych	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient (**)	Cdh	1,0	-	Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0,031	kW	Rated heat output	Psup	1,6	kW
Thermostat-off mode	P _{TO}	-	kW	Type of energy input	electrical		
Standby mode	P _{SB}	0,031	kW				
Crankcase heater mode	P _{CK}	-	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	2.500	m ³ /h
sound power level, indoors/outdoors	L _{WA}	44 / 50	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h
Emissions of nitrogen oxides	NO _x	-	mg/kWh				
For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	η_{wh}	-	%
Daily electricity consumption	Q _{elec}	-	kWh	Daily fuel consumption	Q _{fuel}	-	kWh
Contact details	ait deutschland GmbH Industriestr. 3 95359 Kasendorf Germany						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).							
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							