ENERG Y IJA IE IA
енергия · ενεργεια

100627HM1201

alpha innotec L12 Split-HM 12

	55 °C	35 °C
	A++	A++
	13	12
	10	**12**
	12 kW	12 kW

A+++
A++
A+
A
B
C
D

35 dB

58 dB

2019 **811/2013**

ENERGY

100627HM1201

alpha innotec L12 Split-HM 12

	55 °C	35 °C
	A++	A++
	13	12
	10	**12**
	12 kW	12 kW

A+++
A++
A+
A
B
C
D

35 dB

58 dB

2019 **811/2013**

ENERG Y IJA IE IA

енергия · ενεργεια

100627HM1201

alpha innotec

L12 Split-HM 12 + Splitregler

A++

A+++

A++

A+

A

B

C

D

E

F

G

A++

2015

811/2013

package (heat pumps and combination heater with heat pump) - L12 Split-HM 12 + Splitregler

Seasonal space heating energy efficiency of heat pump (ηs)					❶	132 %
Rated heat output of the heat pump (Prated kW)			10			
Temperature control	Class		VI	***(Table 1)*** +	❷	4,0 %
Supplementary boiler						
package with hot water storage tank	no				*Psup kW (rated heat output of supplementary heater)*	
			ησ % (συπ)			
				(ηs % ***(sup)*** - ❶) x (α_{WP}) = -	❸	%
(αWE: see Table 3)			***(α_{WE})***			
solar contribution		***(A_{Koll} m^2)***		***(ηKoll %)***		
		(V_{Sp} m^3)		***(standstill heat loss of the hot water storage tank in W)***		
				(ηSp: Table 2)		
				((294/P_{rated} x11) x **(A_{Koll} m^2)** + (115/P_{rated} x11) x **(V_{Sp} m^3)**) x 0,45 x (**(ηKoll %)** /100) x **(ηSp)** = +	❹	%
Seasonal space heating energy efficiency of package					❺	136 %
						rounded to the nearest integer

Seasonal space heating energy efficiency class of package

G	F	E	D	C	B	A	A+	A++	A+++
								X	
< 30 %	≥ 30 %	≥ 34 %	≥ 36 %	≥ 75 %	≥ 82 %	≥ 90 %	≥ 98 %	≥ 125 %	≥ 150 %

Seasonal space heating energy efficiency under colder or warmer climate conditions

Seasonal space heating energy efficiency of the heat pump (ηs) under colder climate conditions	109 %
Seasonal space heating energy efficiency of the heat pump (ηs) under warmer climate conditions	183 %

colder ❺	136	-V	23	=	113	warmer ❺	136	+VI	51	=	187

heatpump datasheet:			
manufacturer:	**alpha innotec**		
model:	**L12 Split-HM 12**		
Information concerning energy efficiency class and rated heat output:			
	average / low	average / medium	
energy efficiency class space heater:	A++	A++	-
rated heat output:	12	10	kW
energy efficiency space heater:	174	132	%
annual final energy consumption space heater	5361	6137	kWh
sound power level indoors		35	dB
special precautions concerning assembly, installation or maintenance			
All instructional work in this manual may only be carried out by qualified specialist personnel in compliance with local regulations.			
additional information	low	medium	
rated heat output colder climate	12	13	kW
rated heat output warmer climate	12	12	kW
energy effiency space heater colder climate	140	109	%
energy effiency space heater warmer climate	229	183	%
annual energy consumption space heater colder climate	7920	11461	kWh
annual energy consumption space heater warmer climate	2765	3445	kWh
sound power level outdoors		58	dB

technical data of the temperature controller		
manufacturer:	**alpha innotec**	
model:	**Splitregler**	
controller class	VI	-
contribution of the controller to the energy efficiency space heater	4,0	%

Model				**L12 Split-HM 12**			
Air-to-water heat pump: (yes/no)				yes			
Brine-to-water heat pump: (yes/no)				no			
Water-to-water heat pump: (yes/no)				no			
Low-temperature heat pump: (yes/no)				no			
Equipped with supplementary heater: (yes/no)				no			
combination heater with: (yes/no)				no			
application: (low/medium)				medium			
climate: (colder/average/warmer)				average			
Item	**Symbol**	**Value**	**Unit**	**Item**	**Symbol**	**Value**	**Unit**
Rated heat output	Prated	10	kW	**Seasonal space heating energy efficiency**	ηS	132,0	%
Declared coefficient of performance for part load at indoor temperature 20°C and outdoor temperature Tj				**Declared coefficient of performance for part load at indoor temperature 20°C and outdoor temperature Tj**			
Tj = -7°C	Pdh	8,9	kW	Tj = -7°C	COPd	1,99	-
Tj = +2°C	Pdh	5,5	kW	Tj = +2°C	COPd	3,22	-
Tj = +7°C	Pdh	3,6	kW	Tj = +7°C	COPd	4,61	-
Tj = +12°C	Pdh	5,0	kW	Tj = +12°C	COPd	6,91	-
Tj = bivalent temperature	Pdh	9,2	kW	Tj = bivalent temperature	COPd	1,90	-
Tj = operation limit temperature	Pdh	8,1	kW	Tj = operation limit temperature	COPd	1,92	-
For air-to-water heat pumps: Tj = -15°C (if TOL < -20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C (if TOL < -20°C)	COPd	-	-
Bivalent temperature	T_{biv}	-8	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Pcych	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient (**)	Cdh	1,0	-	Heating water operating limit temperature	WTOL	58	°C
Power consumption in modes other than active mode				**Supplementary heater**			
Off mode	P_{OFF}	0,002	kW	Rated heat output	Psup	1,9	kW
Thermostat-off mode	P_{TO}	0,020	kW	Type of energy input	electrical		
Standby mode	P_{SB}	0,015	kW				
Crankcase heater mode	P_{CK}	0,035	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4.380	m^3/h
sound power level, indoors/outdoors	L_{WA}	35 / 58	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m^3/h
Emissions of nitrogen oxides	NO_X	-	mg/kWh				
For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	η_{wh}	-	%
Daily electricity consumption	Q_{elec}	-	kWh	Daily fuel consumption	Qfuel	-	kWh
Contact details	ait deutschland GmbH Industriestr. 3 95359 Kasendorf Germany						

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

Model				L12 Split-HM 12			
Air-to-water heat pump: (yes/no)				yes			
Brine-to-water heat pump: (yes/no)				no			
Water-to-water heat pump: (yes/no)				no			
Low-temperature heat pump: (yes/no)				no			
Equipped with supplementary heater: (yes/no)				no			
combination heater with: (yes/no)				no			
application: (low/medium)				low			
climate: (colder/average/warmer)				average			
Item	**Symbol**	**Value**	**Unit**	**Item**	**Symbol**	**Value**	**Unit**
Rated heat output	Prated	12	kW	**Seasonal space heating energy efficiency**	ηS	174,0	%
Declared coefficient of performance for part load at indoor temperature 20°C and outdoor temperature Tj				**Declared coefficient of performance for part load at indoor temperature 20°C and outdoor temperature Tj**			
Tj = -7°C	Pdh	10,3	kW	Tj = -7°C	COPd	2,93	-
Tj = +2°C	Pdh	6,3	kW	Tj = +2°C	COPd	4,37	-
Tj = +7°C	Pdh	4,1	kW	Tj = +7°C	COPd	5,53	-
Tj = +12°C	Pdh	4,8	kW	Tj = +12°C	COPd	7,59	-
Tj = bivalent temperature	Pdh	10,2	kW	Tj = bivalent temperature	COPd	2,93	-
Tj = operation limit temperature	Pdh	9,3	kW	Tj = operation limit temperature	COPd	2,68	-
For air-to-water heat pumps: Tj = -15°C (if TOL < -20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C (if TOL < -20°C)	COPd	-	-
Bivalent temperature	T_{biv}	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Pcych	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient (**)	Cdh	1,0	-	Heating water operating limit temperature	WTOL	58	°C
Power consumption in modes other than active mode				**Supplementary heater**			
Off mode	P_{OFF}	0,002	kW	Rated heat output	Psup	2,2	kW
Thermostat-off mode	P_{TO}	0,020	kW	Type of energy input	electrical		
Standby mode	P_{SB}	0,015	kW				
Crankcase heater mode	P_{CK}	0,035	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4.380	m^3/h
sound power level, indoors/outdoors	L_{WA}	35 / 58	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m^3/h
Emissions of nitrogen oxides	NO_X	-	mg/kWh				
For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	η_{wh}	-	%
Daily electricity consumption	Q_{elec}	-	kWh	Daily fuel consumption	Qfuel	-	kWh
Contact details	ait deutschland GmbH Industriestr. 3 95359 Kasendorf Germany						

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.